



- Polypropylene conical entry funnel
- Heat-resistant up to 105 °C
- The entry funnel can also be manufactured from a non-flammable material on request

For conductors of 2 x 0.5-2 x 16 mm² (2 x AWG 20-2 x AWG6)

Material E-Cu, electro-galvanised

Dimensional tolerance acc. to DIN 46228 Part 4

DIN colour code

Packed loose



Type	Ø mm ²	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.5/15D	0.5	AWG 20	14.00	8	1.4		0.15	0.3	11	○ White	500	9037380000
H0.5/16.5D	0.5	AWG 20	16.00	10	1.4		0.15	0.3	13	○ White	500	9037390000
H0.5/18.4D	0.5	AWG 20	18.00	12	1.4		0.15	0.3	15	○ White	500	9037400000
H0.75/15D	0.75	AWG 18	14.00	8	1.7		0.15	0.3	11	● Grey	500	9037410000
H0.75/17D	0.75	AWG 18	16.00	10	1.7		0.15	0.3	13	● Grey	500	9037420000
H0.75/19DS	0.75	AWG 18	19.00	12	1.7		0.15	0.3	21	● Grey	500	9202830000
H0.75/24.5D	0.75	AWG 18	24.00	18	1.7		0.15	0.3	21	● Grey	500	9037430000
H1.0/15D	1	AWG 17	15.00	8	2		0.15	0.3	11	● Red	500	9037440000
H1.0/20D	1	AWG 17	19.00	12	2		0.15	0.3	16	● Red	500	9037450000
H1.0/22DS	1	AWG 17	22.00		2		0.15	0.3	21	● Red	500	9036330000
H1.0/25.6D	1	AWG 17	25.00	18	2		0.15	0.3	22	● Red	500	9037460000
H1.5/16D	1.5	AWG 16	16.00	8	2.2		0.15	0.3	11	● Black	500	9037470000
H1.5/20D	1.5	AWG 16	20.00	12	2.2		0.15	0.3	15	● Black	500	9037480000
H1.5/25.6D	1.5	AWG 16	25.00	18	2.2		0.15	0.3	21	● Black	100	9037490000
H2.5/18.5D	2.5	AWG 14	19.00	10	2.8		0.15	0.4	13	● Blue	500	9037500000
H2.5/20.5D	2.5	AWG 14	21.00	12	2.8		0.15	0.4	15	● Blue	100	9037510000
H2.5/26.5D	2.5	AWG 14	27.00	18	2.8		0.15	0.4	21	● Blue	100	9037520000
H4.0/22D	4	AWG 12	22.00	12	3.5		0.2	0.5	15	● Grey	100	9037530000
H4.0/28D	4	AWG 12	28.00	18	3.5		0.2	0.5	21	● Grey	100	9037540000
H6.0/25D	6	AWG 10	23.00	12	4.5		0.2	0.5	20	● Yellow	100	9037550000
H6.0/29D	6	AWG 10	29.00	18	4.5		0.2	0.5	24	● Yellow	100	9037560000
H10.0/26D	10	AWG 7	24.00	12	5.8		0.2	0.5	17	● Red	100	9037570000
H10.0/24DS	10	AWG 7	24.00	12	6.5		0.2	0.5	17	● Red	100	9018880000
H10.0/30D	10	AWG 7	30.00	18	5.8		0.2	0.5	23	● Red	100	9037580000
H10.0/30DS	10	AWG 7	30.00	18	6.5		0.2	0.5	23	● Red	100	9018890000
H16.0/29D	16	AWG 6	29.00	16	8.3		0.3	0.6	20	● Blue	50	9037590000
H16.0/38D	16	AWG 6	38.00	25	8.3		0.3	0.6	29	● Blue	50	9037600000

DIN colour code

In multi-pack bag



Type	Ø mm ²	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.5/15D	0.5	AWG 20	14.00	8	1.4		0.15	0.3	11	○ White	500	9004780000
H0.75/15D	0.75	AWG 18	14.00	8	1.7		0.15	0.3	11	● Grey	500	9018520000
H1.0/15D	1	AWG 17	15.00	8	2.2		0.15	0.3	12	● Red	500	9018540000
H1.0/20D	1	AWG 17	19.00	12	2		0.15	0.3	16	● Red	500	9004760000
H0.75/17D	0.75	AWG 18	16.00	10	1.7		0.15	0.3	13	● Grey	500	9004770000
H1.5/16D	1.5	AWG 16	16.00	8	2.2		0.15	0.3	11	● Black	500	9004420000
H1.5/20D	1.5	AWG 16	20.00	12	2.2		0.15	0.3	15	● Black	500	9004750000
H2.5/18.5D	2.5	AWG 14	19.00	10	2.8		0.15	0.4	13	● Blue	250	9004430000
H2.5/20.5D	2.5	AWG 14	21.00	12	2.8		0.15	0.4	15	● Blue	100	9004740000
H4.0/22D	4	AWG 12	22.00	12	3.5		0.2	0.5	15	● Grey	100	9004730000
H6.0/25D	6	AWG 10	23.00	12	4.5		0.2	0.5	20	● Yellow	100	9004720000
H10.0/26D	10	AWG 7	26.00	12	5.8		0.2	0.5	17	● Red	100	9004710000