


## Wire-end ferrules with plastic collars, special sizes



- Polypropylene conical entry funnel
  - Heat-resistant up to 105 °C
  - The entry funnel can also be manufactured from a non-flammable material on request
- For conductors of 0.5-2.5 mm<sup>2</sup> Material E-Cu, electro-galvanised  
Dimensional tolerance acc. to DIN 46228 Part 4

### Weidmüller colour code

#### Packed loose



Type	Ø mm <sup>2</sup>	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H 0,34/11 S	0.34	AWG 22	11.00	6	0.85	2.6	0.15	0.4	6	● Turquoise	500	9204090000
H0.5/14S	0.5	AWG 20	14.00	8	1	2.9	0.15	0.25	10	● Orange	500	9004560000
H0.5/14S	0.5	AWG 20	14.00	8	1	2.9	0.15	0.25	10	○ White	500	9004590000
H0.5/16DS	0.5	AWG 20	16.00	10	1	2.9	0.15	0.25	12	○ White	500	9202910000
H0.5/16S	0.5	AWG 20	16.00	10	1	2.9	0.15	0.25	12	● Orange	500	9202900000
H0.75/14 DS	0.75	AWG 18	14.00	8	1.2	3.4	0.15	0.25	10	● Grey	500	9028580000
H0.75/14S	0.75	AWG 18	14.00	8	1.2	3.4	0.15	0.25	10	○ White	500	9025960000
H0.75/14TS	0.75	AWG 18	14.00	8	1.2	3.4	0.15	0.25	10	● LightBlue	500	9018550000
H 0,75/15 S	0.75	AWG 18	15.00	9	1.2	2.8	0.15	0.25	10	● LightBlue	500	9204240000
H1.0/14S	1	AWG 17	14.00	8	1.4	3.5	0.15	0.25	10	● Yellow	500	9025970000
H1.0/14S	1	AWG 17	14.00	8	1.4	3.5	0.15	0.25	10	● Red	500	9018560000
H1.5/12S	1.5	AWG 16	12.00	6	1.7	3.9	0.15	0.25	8	● Red	500	9025690000
H1.5/14S	1.5	AWG 16	14.00	8	1.7	3.9	0.15	0.25	10	● Red	500	9025980000
H1.5/14S	1.5	AWG 16	14.00	8	1.7	3.9	0.15	0.25	10	● Black	500	9025240000
H2.5/12DS	2.5	AWG 14	12.00	6	2.2	4.2	0.15	0.25	8	● Blue	500	9028490000
H2.5/12TS	2.5	AWG 14	12.00	6	2.2	4.2	0.15	0.25	8	● Grey	500	9036200000
H2.5/14S	2.5	AWG 14	14.00	8	2.2	4	0.15	0.25	10	● Blue	500	1333100000
H2.5/14TS	2.5	AWG 14	14.00	8	2.2	4	0.15	0.25	10	● Grey	500	9426770000
H2.5/16DS	2.5	AWG 14	16.00	10	2.2	4.2	0.15	0.25	13	● Blue	500	9036220000
H4.0/20DS	4	AWG 12	20.00	12	2.9	4.7	0.2	0.5	15	● Grey	500	9203630000
H10.0/22S	10	AWG 7	22.00	12	4.6	7.1	0.2	0.6	15	● Ivory	100	9203620000

### Weidmüller colour code

#### In multi-pack bag



Type	Ø mm <sup>2</sup>	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.75/14S	0.75	AWG 18	14.00	8	1.2	3.4	0.15	0.25	10	○ White	500	9025700000
H1.0/14S	1	AWG 17	14.00	8	1.4	3.5	0.15	0.25	10	● Yellow	500	9025710000
H1.5/14DS	1.5	AWG 16	14.00	8	1.7	3.9	0.15	0.25	10	● Black	500	9028360000
H1.5/14S	1.5	AWG 16	14.00	8	1.7	3.9	0.15	0.25	10	● Red	500	9025720000