

Automatic strippers

Automatic strippers

- Strips stranded wires according to DIN VDE 0295, cl. 5
- Partial stripping of insulation; the insulation remains on the wire end
- Change of tools not necessary
- Electric drive
- For small and mid-sized batches

Automatic machines are designed to process wires according to DIN VDE 0295/5, DIN VDE 0281/102 and DIN VDE 0281/103.

Processing of other wire types on request.

Powerstripper 6.0

0.14...6.0 mm²



- Quick and easy adjustment to the respective cross-section
- Stripping length: 3...20 mm
- Min. conductor length: 22 mm + stripping length

Powerstripper 16.0

2.5...16.0 mm²



- Quick and easy adjustment to the respective cross-section
- Stripping length: 3...20 mm
- Min. conductor length: 22 mm + stripping length

Technical data

| Specification | |
|-------------------------|----|
| Stripping range | |
| Conductor length, min. | |
| Pull-off length | |
| Pulse time | |
| Electrical connection | |
| Connection values | |
| Tool data | |
| Length / Width / Height | mm |
| Weight | kg |
| Note | |

Ordering data

| Version |
|---------|
| |
| |
| |
| Note |

| POWERSTRIPPER 6,0 | | |
|---|--|--|
| 0.14 - 6.0 mm ² (~AWG 26...10) | | |
| 22 mm + stripping length | | |
| 3...20 mm | | |
| approx. 0.5 s | | |
| 220 V / 50 Hz | | |
| 46 VA | | |
| | | |
| 295 / 190 / 190 | | |
| 8.8 | | |

| Type | Qty. | Order No. |
|-------------------|------|------------|
| POWERSTRIPPER 6,0 | 1 | 9028510000 |
| | | |
| | | |

| POWERSTRIPPER 16,0 | | |
|--|--|--|
| 2.5 - 16 mm ² (~AWG 14...6) | | |
| 22 mm + stripping length | | |
| 3...20 mm | | |
| approx. 1.5 s | | |
| 220 V / 50 Hz | | |
| 46 VA | | |
| | | |
| 295 / 190 / 230 | | |
| 11 | | |

| Type | Qty. | Order No. |
|--------------------|------|------------|
| POWERSTRIPPER 16,0 | 1 | 9028480000 |
| | | |
| | | |