

Automatic strippers

- Strips stranded wires according to DIN VDE 0295, cl. 5
- Partial stripping of insulation; the insulation remains on the wire end
- Integrated sensing system for determining the wire cross-section and the resulting cutting depth
- Electric drive
- Change of tools not necessary
- For small and mid-sized batches
- Automatic adjustment to the appropriate wire cross-section

Automatic machines are designed to process wires according to DIN VDE 0295/5, DIN VDE 0281/102 and DIN VDE 0281/103.

Processing of other wire types on request.

Powerstripper auto 2.5

0.5...2.5 mm²



Power stripper auto 2.5...20

- Stripping length from 3... 20 mm
- Min. conductor length 22 mm plus stripping length

Powerstripper auto 16.0

4.0 to 16 mm²



Power stripper auto 16...20

- Stripping length from 3... 20 mm
- Min. conductor length 22 mm plus stripping length

Technical data

Specification	
Stripping range	
Conductor length, min.	
Pull-off length	
Pulse time	
Electrical connection	
Connection values	
Tool data	
Length / Width / Height	mm
Weight	kg
Note	

Ordering data

Version
Note

POWERSTRIPPER auto 2,5...20		
0.5 - 2.5 mm ² (~AWG 20...14)		
22 mm + stripping length		
1...20 mm		
approx. 0.5 s		
220 V / 50 Hz		
46 VA		
295 / 190 / 205		
9		

Type	Qty.	Order No.
POWERSTRIPPER ao 2,5-20	1	9027270000
Note		

POWERSTRIPPER auto 16...20		
4 - 16 mm ² (~AWG 12...6)		
22 mm + stripping length		
1...20 mm		
approx. 1.5 s		
220 V / 50 Hz		
46 VA		
295 / 190 / 230		
11		

Type	Qty.	Order No.
POWERSTRIPPER ao 16-20	1	9027290000
Note		