### Crimping tools for other

#### contacts

- Ratchet for precise crimping
- Release option in the event of incorrect operation
- With end stop for exact positioning of the contacts
- Tested according to DIN EN 60352 Part 2

# HTI 15



For PVC-, PC- and polyamide-insulated connectors

• ~AWG 21...14

HTI 15

• Double-crimp profile, for crimping contact and insulation in one step





For uninsulated cable lugs and connectors

- ~AWG 21...10
- Rolled cable lugs, for example acc. to DIN 46234
- Tubular cable lugs
- Pin cable lugs
- Parallel and serial connectors
- Indent crimping
- Alternatively available with or without pivoting end stop





## Technical data

Description of contact	
Type of contact	
Crimping range	mm <sup>2</sup>
Crimping range 1 (with multiple crimping positions)	mm <sup>2</sup>
Crimping range 2 (with multiple crimping positions)	mm <sup>2</sup>
Crimping range 3 (with multiple crimping positions)	mm <sup>2</sup>
Plug width	mm
Tool data	
Length	mm
Weight	g
Note	

### Ordering data

Version

Insulated connector
0.52.5
0.51.5
1.12.5
200
434

Uty.	Order No.
1	9014400000
1	9017430000
	1 1

HTN 21	HTN 21 M. AN.
Uninsulated connection	Uninsulated connection
0.56	0.56
0.51.5	0.51.5
1.12.5	1.12.5
2.66	2.66
200	200
427	427
End stop for secure contact position	oning in tool

Туре	Qty.	Order No.
HTN 21	1	9014610000
HTN 21 ZERT	1	9017380000
HTN 21 M. AN	1	9014100000
HTN 21 M. AN ZERT	1	9017170000

Note

Additional accessories can be found in Chapter J

Crimping