Crimping tools for wire end ferrules

- For wire-end ferrules with and without plastic collars, according to DIN 46228 Part 1 and Part 4 · Ratchet for precise crimping
- Release option in the event of incorrect operation

PZ 1.5



- Only one die for the whole cross-section range
- Crimp complies with Euro-Norm EN 60947-1
- Wire-end ferrule insertion from the front



- ~AWG 26...10
- Only one die for the whole cross-section range
- Wire-end ferrule insertion from the side

Crimping





Technical data

Description of contact			
Type of contact			
Crimping range	mm ²		
Crimping range 1 (with multiple crimping positions)	mm ²		
Crimping range 2 (with multiple crimping positions)	mm ²		
Crimping range 3 (with multiple crimping positions)	mm ²		
Crimping range 4 (with multiple crimping positions)	mm ²		
Crimping range 5 (with multiple crimping positions)	mm ²		
Tool data			
Length	mm		
Weight	g		
Note			
Ordering data			
Version			

Wire-end ferrules with/without plastic collars 0.14...1.5 170 170

PZ 1.5

Qty.	Order No.
1	9005990000
1	9017310000
	Qty. 1

Wire-er	nd ferrules with/without plastic collars	3
0.146	· · ·	
180		
380		

Type Qty.	Order No.
PZ 6 HEX 1	9013650000
PZ 6 HEX Zert 1	9017920000
Additional accessories can be found in Chapter J	

Note