## Crimping tools for wire end ferrules

- For wire-end ferrules with and without plastic collars, according to DIN 46228 T.1 and T.4
- Ratchet for precise crimping
- Release option in the event of incorrect operation

## PZ 3



• Only one die for the whole cross-section range

• Wire-end ferrule insertion from the front



PZ 6 roto

• Rotating die enables wire-end ferrule insertion from the front or side





## Technical data

Description of contact	
Type of contact	
Crimping range	mm <sup>2</sup>
Crimping range 1 (with multiple crimping positions)	mm <sup>2</sup>
Crimping range 2 (with multiple crimping positions)	mm <sup>2</sup>
Crimping range 3 (with multiple crimping positions)	mm <sup>2</sup>
Crimping range 4 (with multiple crimping positions)	mm <sup>2</sup>
Crimping range 5 (with multiple crimping positions)	mm <sup>2</sup>
Tool data	
Length	mm
Weight	g
Note	
Ordering data	
Version	

0.5...6 200 426

Wire-end ferrules with/without plastic collars

PZ 3

Туре	Qty.	Order No.
PZ 3	1	0567300000
PZ 3 ZERT	1	9017360000
Additional accessories can be found in Chapter	1	

PZ 6 ro	oto
Wire-er	nd ferrules with/without plastic collars
0.146	3
200	
428	

Туре	Qty.	Order No.
PZ 6 Roto	1	9014350000
PZ 6 ROTO ZERT	1	9017440000
Additional accessories can be found in Chapter J		

D

Note