


## Wire-end ferrules with plastic collars



- Polypropylene conical entry funnel
- Heat-resistant up to 105 °C
- The entry funnel can also be manufactured from a non-flammable material on request

For conductors from 0.14-150 mm<sup>2</sup> (AWG 26-300MCM)

Material E-Cu, electro-galvanised

Dimensional tolerance acc. to DIN 46228 Part 4

### Other colour code

#### Packed loose



Type	Ø mm <sup>2</sup>	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.25/10T	0.25	AWG 24	10.00	6	0.8	1.8	0.15	0.25	8	● Yellow	500	9021010000
H0.25/12T	0.25	AWG 24	12.00	8	0.8	1.8	0.15	0.25	10	● Yellow	500	9021020000
H0.5/12D	0.5	AWG 20	12.00	6	1	2.6	0.15	0.25	8	○ White	500	9019000000
H0.5/14D	0.5	AWG 20	14.00	8	1	2.6	0.15	0.25	10	○ White	500	9019010000
H0.5/16D	0.5	AWG 20	16.00	10	1	2.6	0.15	0.25	12	○ White	500	9019020000
H0.75/12D	0.75	AWG 18	12.00	6	1.2	2.8	0.15	0.25	8	● Grey	500	9019030000
H0.75/14	0.75	AWG 18	14.00	8	1.2	2.8	0.15	0.25	10	● LightBlue	500	9021040000
H0.75/16T	0.75	AWG 18	16.00	10	1.2	2.8	0.15	0.25	12	● LightBlue	500	9021050000
H0.75/18T	0.75	AWG 18	18.00	12	1.2	2.8	0.15	0.25	14	● LightBlue	500	9021060000
H1.0/16D	1	AWG 17	16.00	10	1.4	3	0.15	0.25	12	● Red	500	9019100000
H1.0/18D	1	AWG 17	18.00	12	1.4	3	0.15	0.25	15	● Red	500	9019110000
H1.5/14D	1.5	AWG 16	14.00	8	1.7	3.5	0.15	0.25	10	● Black	500	9019120000
H1.5/16D	1.5	AWG 16	16.00	10	1.7	3.5	0.15	0.25	12	● Black	500	9019130000
H1.5/18D	1.5	AWG 16	18.00	12	1.7	3.5	0.15	0.25	15	● Black	500	9019140000
H1.5/24D	1.5	AWG 16	24.00	18	1.7	3.5	0.15	0.25	20	● Black	500	9019150000
H2.5/14T	2.5	AWG 14	15.00	8	2.2	4.2	0.15	0.25	10	● Grey	500	9021070000
H2.5/18T	2.5	AWG 14	19.00	12	2.2	4.2	0.15	0.25	14	● Grey	500	9021080000
H2.5/24T	2.5	AWG 14	25.00	18	2.2	4.2	0.15	0.25	20	● Grey	500	9021090000
H4.0/17T	4	AWG 12	18.00	10	2.8	4.8	0.2	0.3	12	● Orange	500	9021100000
H4.0/20T	4	AWG 12	20.00	12	2.8	4.8	0.2	0.3	14	● Orange	500	9021110000
H4.0/26T	4	AWG 12	26.00	18	2.8	4.8	0.2	0.3	20	● Orange	100	9021120000
H6.0/20T	6	AWG 10	20.00	12	3.5	6.3	0.2	0.3	14	● Green	100	9021130000
H6.0/26T	6	AWG 10	26.00	18	3.5	6.3	0.2	0.3	20	● Green	100	9021140000
H10.0/22T	10	AWG 7	22.00	12	4.5	7.6	0.2	0.4	15	● Brown	100	9021150000
H10.0/28T	10	AWG 7	28.00	18	4.5	7.6	0.2	0.4	21	● Brown	100	9021160000
H16.0/24T	16	AWG 6	22.00	12	5.8	8.8	0.2	0.4	15	○ White	100	9021170000
H16.0/28T	16	AWG 6	28.00	18	5.8	8.8	0.2	0.4	21	○ White	100	9021180000
H25.0/30T	25	AWG 3	30.00	16	7.3	11.2	0.2	0.4	18	● Black	50	9021190000
H25.0/36T	25	AWG 3	36.00	22	7.3	11.2	0.2	0.4	24	● Black	50	9021200000

### Other colour code

#### In multi-pack bag



Type	Ø mm <sup>2</sup>	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.14/10T	0.14	AWG 26	10.00	6	0.6	1.5	0.15	0.25	8	● Brown	500	9028250000
H0.25/10T	0.25	AWG 24	10.00	6	0.8	1.8	0.15	0.25	8	● Yellow	500	9021210000
H0.25/12T	0.25	AWG 24	12.00	8	0.8	1.8	0.15	0.25	10	● Yellow	500	9021220000
H0.5/14D	0.5	AWG 20	14.00	8	1	2.6	0.15	0.25	10	○ White	500	9019400000
H0.75/14T	0.75	AWG 18	14.00	8	1.2	2.8	0.15	0.25	10	● Light Blue	500	9021230000
H1.0/14D	1	AWG 17	14.00	8	1.4	3	0.15	0.25	10	● Red	500	9019420000
H1.5/14D	1.5	AWG 16	14.00	8	1.7	3.5	0.15	0.25	10	● Black	500	9019430000
H2.5/14T	2.5	AWG 14	15.00	8	2.2	4.2	0.15	0.25	10	● Grey	500	9021240000
H4.0/17T	4	AWG 12	18.00	10	2.8	4.8	0.2	0.3	12	● Orange	250	9021250000

### Other colour code

#### Strips of linked wire-end ferrules



Type	Ø mm <sup>2</sup>	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.5/14D	0.5	AWG 20	14.00	8	1	2.6	0.15	0.25	10	○ White	500	9004280000
H0.75/14T	0.75	AWG 18	14.00	8	1.2	2.8	0.15	0.25	10	● Light Blue	500	9004310000
H1.0/14D	1	AWG 17	14.00	8	1.4	3	0.15	0.25	10	● Red	500	9004330000
H1.5/14D	1.5	AWG 16	14.00	8	1.7	3.2	0.15	0.25	10	● Black	500	9004350000
H2.5/14T	2.5	AWG 14	14.00	8	2.2	4	0.15	0.25	11	● Grey	500	9004370000